



FEATURES

- Embedded ^{241}Am source for energy spectrum stabilization against temperature changes and aging
- 1024 channels spectrum analysis
- Effluent trapping of both molecular and organic forms of iodine
- Can be used as temporary bypass for IM 201S or IM 201L to maintain full monitoring capability during maintenance

IM 201M Mobile Iodine Monitor

The IM 201M monitor forms part of the RAMSYS product line.

It has been developed to continuously measure the gamma volumetric activity of radioactive iodine sample, in both molecular and organic forms (methyl iodine), contained in air drawn from stacks, ventilation ducts or working areas.

An NaI scintillation detector faces the activated charcoal cartridge in which radioactive iodine is trapped. The proximity of the detector and the cartridge, enclosed within a $4\pi/5$ cm ($4\pi/2$ in) lead shielding, serves to optimize detection efficiency. A radioactive ^{241}Am source built into the NaI crystal allows compensation of temperature and aging related drifts. The spectrometry capability, based on a 1024 channel spectrum analysis, allows radio iodine isotope localization.

APPLICATIONS

- Effluent release monitoring
- Radioprotection of workers
 - Containment atmosphere
 - Control room air, etc.
- Operational process monitoring

RELATED MONITORS

- IM 201L: "light" version
- IM 201S: seismically qualified version
- PING 206S: version with particulate and noble gas
- PIM 206S: version with particulate

radiation monitoring
systems

A Mirion Technologies Division

Featuring:



PHYSICAL CHARACTERISTICS

- Radiation detected: gamma
- Detector: 1^{1/4}"x1" NaI(Tl) scintillator + PM
- Iodine cartridge: 57.7 mm (2.27 in)
- Energy range: 100 keV to 3 MeV
- Typical energy windows: 314 - 414 keV (¹³¹I, E_γ 364.5 keV)
- 1024 channels spectrum
- Typical measurement range: 3.7 to 3.7 10⁺⁶ Bq/m³ (10⁻¹⁰ to 10⁻⁴ μCi/cc)

ENVIRONMENTAL CHARACTERISTICS

- Long term temperature: +10°C to +40°C (+50°F to +104°F)
- Maximum periodic ambient temperature: +0°C to +55°C (+32°F to +131°F)
- MTBF: > 50 000 hours, with preventive maintenance
- TID: 100 Gy (10⁺⁴ rad)

PNEUMATIC CHARACTERISTICS

- Standard flow rate: 35 l/min (1.24 scfm)
- Pressure drop: according to the filter dust loading

MECHANICAL CHARACTERISTICS

- Dimensions: 1406 mm x 520 mm x 700 mm (55.4 in x 20.5 in x 27.6 in)
- Weight: ~ 200 kg (~ 441 lb)
- Color: gray RAL 7030 (decontaminable paint)
- Inlet tube connection: Ø 12 mm OD (1/2 in)

ELECTRICAL CHARACTERISTICS

- Power supply: 230 Vac – 50 Hz or 120 Vac – 60 Hz
- Data link outputs: 1 RS232 and 2 isolated RS485
- Alarm relays: 3 SPDT relays
- I/O: 2 isolated analog outputs and 1 isolated analog input (0/4-20 mA)

SIGNALING

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: 3 lights (red, yellow, green)

REFERENCE STANDARDS

- Nuclear: IEC60761, IEC61171
- EMC: 2006/95/CE and 2004/108/CE, IEC61000-6-2 and IEC61000-6-4

VERSIONS

- 230 Vac or 120 Vac
- With or without dust filter holder
- With or without output dust filter

ACCESSORIES

- Calibration tools
- Software
- USB converters



MIRION
TECHNOLOGIES

Radiation Monitoring Systems
Division

MGP Instruments SA
BP 1
FR-13113 Lamanon
France

T +33 (0) 4 90 59 59 59
F +33 (0) 4 90 59 55 18

MGP Instruments Inc.
5000 Highlands Parkway
Suite 150
Smyrna, GA 30082
USA

T +1.770.432.2744
F +1.770.432.9179

MGP Instruments GmbH
Landsberger Strasse 328a
DE-80687 Munich
Germany

T +49 (0) 89515 13-0
F +49 (0) 89515 13 169

www.mirion.com
144105EN-A