



FEATURES

- Wide measurement range
- Can be used for various types of application
- Minimal periodic maintenance
- 1E qualification and embedded safety related software
- Available under 10 CFR 50 App. B, ASME NQA-1 and IEC61226 programs for safety related applications

SAM 204K Spectrum Analysis Monitor

The SAM 204K forms part of the RAMSYS product line. It has been developed to detect gamma radiations and provide gamma spectra analysis with identification of isotopes.

The SAM 204K is designed for continuous unattended operation and can cover most of the gamma measurement ranges required by regulations and industry guidelines.

Four sizes of detector are available which make this monitor very efficient and reliable, with high sensitivity, wide measurement range and fast response time.

APPLICATIONS

- Effluent release monitoring
- Operational process monitoring

RELATED MONITORS

- SAM 201K: version with 1¼"x1" NaI(Tl) detector
- SAM 202K: version with 3"x2" NaI(Tl) detector
- SAM 203K: version with 2"x2" NaI(Tl) detector

radiation monitoring
systems

A Mirion Technologies Division

Featuring:



PHYSICAL CHARACTERISTICS

- Radiation detected: gamma
- Detector: 3"x3" NaI(Tl) scintillator + PMT
- Energy range: 100 keV to 7 MeV
- Spectrometry analysis: 1024 channels
- Typical measurement range: 6 decades between $3.7 \cdot 10^{+2}$ to $3.7 \cdot 10^{+12}$ Bq/m³ (10^{-8} to 10^{+2} μ Ci/cc)

ENVIRONMENTAL CHARACTERISTICS

- Long term temperature: +10°C to +40°C (+50°F to +104°F)
- Periodic temperature: -5°C to +55°C (+23°F to +131°F)
- MTBF: > 20 000 hours
- TID (processing unit): 100 Gy (10^{+4} rad)
- TID (detector): 10^{+3} Gy (10^{+5} rad)
- Protection index: IP65 and IK07

MECHANICAL CHARACTERISTICS

- Dimensions:
 - Processing unit: 390 mm x 196 mm x 187 mm (15.3 in x 7.7 in x 7.3 in)
 - Detector: 329 mm x 388 mm x 513 mm (13 in x 15.3 in x 20.2 in)
- Weight:
 - Processing unit: 8 kg (17.6 lb)
 - Detector: 220 kg (485 lb)
- Color: gray RAL 7030 (decontaminable paint)

ELECTRICAL CHARACTERISTICS

- Power supply: 230 Vac – 50 Hz or 120 Vac – 60 Hz
- Data link outputs: 1 RS232 and 2 isolated RS485
- Alarm relays: 3 SPDT relays
- I/O: 2 isolated analog outputs and 1 isolated analog input (0/4–20 mA)

SIGNALING (Applicable to LPDU only)

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: 3 lights (red, yellow, green)

REFERENCE STANDARDS

- Environmental: IEC60780, IEEE323
- Seismic: IEC60980, IEEE344
- EMC: 2006/95/CE, 2004/108/CE, EPRI 102323, MIL STD 461 E, IEC61000-6-2 and IEC61000-6-4

VERSIONS

- 230 Vac or 120 Vac
- LPDU or LPU
- Without protection, 2 $\pi/5$ cm (2 $\pi/2$ in) or 4 $\pi/5$ cm (4 $\pi/2$ in) detector lead shield
- With or without RS485 junction box
- Detector cable length: from 20 m (65.6 ft) to 100 m (328 ft)
- Junction box cable length: 2 m (6.56 ft), 5 m (16.4 ft) or 10 m (32.8 ft)

ACCESSORIES

- Calibration tools
- Software
- USB converters
- Seismic qualified wall mounting bracket
- Detection sub-assembly support



MIRION
TECHNOLOGIES

Radiation Monitoring Systems
Division

Mirion Technologies (MGPI) SA
Route d'Eyguières
FR-13113 Lamanon
France

T +33 (0) 4 90 59 59 59
F +33 (0) 4 90 59 55 18

Mirion Technologies (MGPI) Inc
5000 Highlands Parkway
Suite 150
Smyrna, GA 30082
USA

T +1 770 432 2744
F +1 770 432 9179

Mirion Technologies (MGPI H&B) GmbH
Landsberger Strasse 328a
DE-80687 Munich
Germany

T +49 (0) 89 515 13 0
F +49 (0) 89 515 13 169

Mirion Commercial (Beijing) Co., Ltd.
Shanghai Jiangchang Commercial Branch
Room 801, 78 Jiangchang SanLu
Zhabei District, Shanghai 200436
PR of China

T +86 21 6180 6920
F +86 21 6180 6924

www.mirion.com
144427EN-E