



FEATURES

- One hand operation
- Stand up base holder
- Automatic internal diagnostics
- Portable, lightweight and compact
- Large, easy to read, 7- segment, 4 digit LCD display panel
- Ergonomically designed to function using only 3 push-buttons
- Fast time responses while keeping the reading fluctuations at a minimum.

Functions

- Automatic internal monitor and detector test
- Dose rate and accumulated dose (mR and μ Sv)
- Detector failure, overflow and low battery alarms
- Set up thresholds
- LED indicator flash with each incident radiation pulse
- Dead time correction
- Optional external DC power or charger

The versatile RAM GAM-1 monitor is a state of the art, compact, portable, lightweight highly sensitive meter, designed to maintain the highest safety standards in Nuclear Power Plants, Nuclear Research Centers, Nuclear materials Transporting facilities, Nuclear Medical, Radiochemistry, Radiography and Health Physics centers. The intrinsic CMOS microprocessor facilitates smooth software control and allows for easy upgrading of the instrument's capacity for measuring a wide range of measurement values.



health physics

A Mirion Technologies Division

Featuring:



Technical Data

Detector	Energy compensated GM tube (ZP1201 or equivalent)
Measuring range	0.05 mR/h to 999 mR/h (0.5 μ Sv/h to 9999 μ Sv/h)
Display range	<i>Dose rate:</i> 0.01 mR/h to 999 mR/h (0.1 μ Sv/h to 9999 μ Sv/h) <i>Accumulated Dose:</i> 0.01 mR to 999 KmR (0.1 μ Sv/h to 999 K μ Sv/h)
Display	<i>LCD readout showing :</i> 4 digits for accurate and easy readout detector failure low battery overflow Threshold LED Indicator flash for count rate
Audio	Internally mounted piezo-electric element
Measuring Units	mR/h and mR or μ Sv/h and μ Sv
Power source	One 9 volt cell battery supplying \pm 50 hours of continuous operation. Automatic battery check under full load
Temperature range	Operation: -10 deg C to +50 deg C (15F - 122F) Storage -20 deg C to +60 deg C (-5F to 140F)
Humidity range	- 40% to 95% RH (non-condensing)
Casing	High impact resistant plastic (ABS)
Dimensions	13cm X 7.2 cm X 3.4 sm (5.12" X 2.83" x 1.34")
Weight	280 gr (0.62 lb)
Sensitivity (¹³⁷ Cs)	17 cps/mR/h
Accuracy	\pm 15% of reading within the measured range
Energy range	50 keV to 1.3 MeV
Energy dependence	\pm 20% related to ¹³⁷ Cs
Angular dependence	Less than \pm 20% for \pm 45 ⁰ of preferred direction.



MIRION Health Physics
TECHNOLOGIES Division

www.mirion.com
144269EN-A

MGP Instruments Inc.
5000 Highlands Parkway
Suite 150
Smyrna Georgia 30082
USA
T +1.770.432.2744
F +1.770.432.9179

MGP Instruments SA
BP 1
F-13113 Lamanon
France
T +33 (0) 4 90 59 59 59
F +33 (0) 4 90 59 55 18

RADOS Technology Oy
P.O. Box 506
FIN-20101 Turku
Finland
T +358 2 468 4600
F +358 2 468 4601

RADOS Technology GmbH
Ruhstrassen 49
DE-22761 Hamburg
Germany
T +49 (0) 40 851 9340
F +49 (0) 40 851 93 256