


# BT134 SERIES

## TO-126 Plastic-Encapsulate Thyristors



### GENERAL DESCRIPTION

Glass passivated triacs in a plastic envelope, intended for use in applications requiring high bidirectional transient and blocking voltage capability and high thermal cycling performance. Typical applications include motor control, industrial and domestic lighting, heating and static switching.



TO-126



### QUICK REFERENCE DATA

SYMBOL	PARAMETER	MAX.	MAX.	MAX.	UNIT
	BT134-	500	600	800	
	BT134-	500F	600F	800F	
	BT134-	500G	600G	800G	
$V_{DRM}$	Repetitive peak off-state voltages	500	600	800	V
$I_{T(RMS)}$	RMS on-state current	4	4	4	A
$I_{TSM}$	Non-repetitive peak on-state current	25	25	25	A

### LIMITING VALUES

Limiting values in accordance with the Absolute Maximum System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.			UNIT
				-500 500 <sup>1</sup>	-600 600 <sup>1</sup>	-800 800	
$V_{DRM}$	Repetitive peak off-state voltages		-				V
$I_{T(RMS)}$	RMS on-state current	full sine wave; $T_{mb} \leq 107^\circ C$	-				A
$I_{TSM}$	Non-repetitive peak on-state current	full sine wave; $T_j = 25^\circ C$ prior to surge		4			
$I^2t$	$I^2t$ for fusing	$t = 20$ ms	-				A
$dI_T/dt$	Repetitive rate of rise of on-state current after triggering	$t = 16.7$ ms	-				A <sup>2</sup> s
		$t = 10$ ms	-				
		$I_{TM} = 6$ A; $I_G = 0.2$ A;					
		$dI_G/dt = 0.2$ A/ $\mu$ s					
$I_{GM}$	Peak gate current	T2+ G+	-	50			A/ $\mu$ s
$V_{GM}$	Peak gate voltage	T2+ G-	-	50			A/ $\mu$ s
$P_{GM}$	Peak gate power	T2- G-	-	50			A/ $\mu$ s
$P_{G(AV)}$	Average gate power	T2- G+	-	10			A/ $\mu$ s
$T_{stg}$	Storage temperature		-	2			A
$T_j$	Operating junction temperature	over any 20 ms period	-	5			V
			-40	5			W
				0.5			W
				150			°C
				125			°C

<sup>1</sup> Although not recommended, off-state voltages up to 800V may be applied without damage, but the triac may switch to the on-state. The rate of rise of current should not exceed 3 A/ $\mu$ s.

## BT134 series

### THERMAL RESISTANCES

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$R_{th\ j\rightarrow mb}$	Thermal resistance junction to mounting base	full cycle	-	-	3.0	K/W
$R_{th\ j\rightarrow a}$	Thermal resistance junction to ambient	half cycle in free air	-	100	3.7	K/W

### STATIC CHARACTERISTICS

$T_j = 25^\circ C$  unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.		UNIT
					...F	...G	
$I_{GT}$	Gate trigger current	$V_D = 12 V; I_T = 0.1 A$ $T2+ G+$ $T2+ G-$ $T2- G-$ $T2- G+$	-	5	35	25	mA
			-	8	35	25	mA
			-	11	35	25	mA
			-	30	70	70	mA
$I_L$	Latching current	$V_D = 12 V; I_{GT} = 0.1 A$ $T2+ G+$ $T2+ G-$ $T2- G-$ $T2- G+$	-	7	20	20	mA
			-	16	30	30	mA
			-	5	20	20	mA
			-	7	30	30	mA
$I_H$	Holding current	$V_D = 12 V; I_{GT} = 0.1 A$	-	5	15	15	mA
			-	5	15	30	mA
$V_T$ $V_{GT}$	On-state voltage Gate trigger voltage	$I_T = 5 A$ $V_D = 12 V; I_T = 0.1 A$ $V_D = 400 V; I_T = 0.1 A;$ $T_j = 125^\circ C$	-	1.4	1.70	V	
			-	0.7	1.5	V	
$I_D$	Off-state leakage current	$V_D = V_{DRM(max)}$ $T_j = 125^\circ C$	0.25	0.4	-	V	
			-	0.1	0.5	mA	

### DYNAMIC CHARACTERISTICS

$T_j = 25^\circ C$  unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN.			TYP.	MAX.	UNIT
$dV_D/dt$	Critical rate of rise of off-state voltage	$V_{DM} = 67\% V_{DRM(max)}$ $T_j = 125^\circ C$ ; exponential waveform; gate open circuit	100	50	200	250	-	V/ $\mu$ s
$dV_{com}/dt$	Critical rate of change of commutating voltage	$V_{DM} = 400 V$ ; $T_j = 95^\circ C$ $I_{T(RMS)} = 4 A$ $dl_{com}/dt = 1.8 A/ms$ ; gate open circuit	-	-	10	50	-	V/ $\mu$ s
$t_{gt}$	Gate controlled turn-on time	$I_{TM} = 6 A$ ; $V_D = V_{DRM(max)}$ $I_G = 0.1 A$ $dl_G/dt = 5 A/\mu s$	-	-	-	2	-	$\mu$ s

## BT134 series




Fig.1. Maximum on-state dissipation,  $P_{tot}$ , versus rms on-state current,  $I_{T(RMS)}$ , where  $\alpha$  = conduction angle.




Fig.4. Maximum permissible rms current  $I_{T(RMS)}$ , versus mounting base temperature  $T_{mb}$ .




Fig.2. Maximum permissible non-repetitive peak on-state current  $I_{TSM}$ , versus pulse width  $t_p$ , for sinusoidal currents,  $t_p \leq 20\text{ms}$ .




Fig.5. Maximum permissible repetitive rms on-state current  $I_{T(RMS)}$ , versus surge duration, for sinusoidal currents,  $f = 50\text{ Hz}$ ;  $T_{mb} \leq 107^\circ\text{C}$ .




Fig.3. Maximum permissible non-repetitive peak on-state current  $I_{TSM}$ , versus number of cycles, for sinusoidal currents,  $f = 50\text{ Hz}$ .




Fig.6. Normalised gate trigger voltage  $V_{GT}(T_j)/V_{GT}(25^\circ\text{C})$ , versus junction temperature  $T_j$ .

## BT134 series




Fig.7. Normalised gate trigger current  $I_{GT}(T_j)/I_{GT}(25^\circ\text{C})$ , versus junction temperature  $T_j$ .




Fig.10. Typical and maximum on-state characteristic.




Fig.8. Normalised latching current  $I_L(T_j)/I_L(25^\circ\text{C})$ , versus junction temperature  $T_j$ .




Fig.11. Transient thermal impedance  $Z_{th,j-mb}$ , versus pulse width  $t_p$ .




Fig.9. Normalised holding current  $I_H(T_j)/I_H(25^\circ\text{C})$ , versus junction temperature  $T_j$ .




Fig.12. Typical commutation  $dV/dt$  versus junction temperature, parameter commutation  $dl_7/dt$ . The triac should commutate when the  $dV/dt$  is below the value on the appropriate curve for pre-commutation  $dl_7/dt$ .