




DONGGUAN NANJING ELECTRONICS LTD.,
Surface Mount Transient Voltage Suppressor

ESD5Z5.0C

Features

- ◆ 150 Watts peak pulse power ($t_p = 8/20\mu s$)
- ◆ Transient protection for high speed data lines to
IEC 61000-4-2 (ESD) $\pm 15kV$ (air), $\pm 8kV$ (contact)
IEC 61000-4-4 (EFT) 40A (5/50ns)
- ◆ Protects One Power or I/O Port
- ◆ Low leakage current
- ◆ Low operating and clamping voltages
- ◆ Solid-state silicon avalanche technology



Applications

- ◆ Cell Phone Handsets and Accessories
- ◆ Microprocessor based equipment
- ◆ Portable Instrumentation
- ◆ Personal Digital Assistant (PDA)





Maximum Rating @ $T_a = 25^\circ C$ unless otherwise specified

Symbol	Parameter	Ratings	Units
P_{PK}	Peak Pulse Power ($t_p = 8/20\mu s$)	150	Watts
T_L	Lead Soldering Temperature	260(10sec.)	$^\circ C$
T_J	Operating Temperature	-55 to +125	$^\circ C$
T_{STG}	Storage Temperature	-55 to +150	$^\circ C$

Electrical Characteristics @ $T_a = 25^\circ C$ unless otherwise


Parameter	Marking	$V_{RWM} @ I_R$		$V_{BR} @ I_{mA}$	$V_C @ 1A$	$V_C @ I_{PP}$		C_J
		V	μA	V	V	V	A	pF
			MAX	MIN	MAX	MAX		MAX
ESD5Z5.0C		5	1	6	9.8	15	8	30

Typical Characteristics@ Ta=25°C unless otherwise specified



Soldering Parameters


Reflow Condition		Fb – Free assembly
Pre Heat	- Temperature Min ($T_{s(Min)}$)	150°C
	- Temperature Max ($T_{s(Max)}$)	200°C
	- Time (Min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus) Temp (T_L) to peak		3°C/second Max
$T_{s(Max)}$ to T_L - Ramp-up Rate		3°C/second Max
Reflow	- Temperature (T_L) (Liquidus)	217°C
	- Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_p)		250 ^{+0/-5} °C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second Max
Time 25°C to peak Temperature (T_p)		8 minutes Max.
Do not exceed		260°C




Package Outline

Plastic surface mounted package

SOD523



Soldering Footprint



Package And Marking Information

Device	Package	Shipping	Reel Size
ESD5Z5.0C	SOD523	3000/Reel	7 inch